

PULL-STROKE SAWS

JAPAN PULL™ R-SAW



BLADE						MATERIAL SUITABILITY INDEX					
	CUT	BLADE LENGTH	TOOTH PITCH	TPI	BLADE THICKNESS KERF WIDTH						
① MGB-300FB JAPANESE-CUTTING TEMPERING DISCO DRIVE IMPULSED BLADE COAT (PULBLC)	STANDARD CUT	11.8 in (300 mm)	0.08 in (2.15 mm)	13 TPI	0.03 in. (0.7 mm)		★	★★	★★★	★★★	
② GNB-300 JAPANESE-CUTTING TEMPERING DISCO DRIVE IMPULSED BLADE COAT (PULBLC)					0.05 in. (1.15 mm)		★	★★	★★★	★★★	
③ GNB-265 JAPANESE-CUTTING TEMPERING DISCO DRIVE IMPULSED BLADE COAT (PULBLC)	FINE CUT	10.4 in (265 mm)	0.07 in (1.75 mm)	16 TPI	0.02 in. (0.6 mm)		★★	★★★	★★★	★	
④ GNB-265ST JAPANESE-CUTTING TEMPERING DISCO DRIVE IMPULSED BLADE COAT (PULBLC)		9.1 in (230 mm)			0.04 in. (0.9 mm)		★★	★★★	★★★	★	
⑤ GNB-250 JAPANESE-CUTTING TEMPERING DISCO DRIVE IMPULSED BLADE COAT (PULBLC)	EXTRA FINE CUT	9.8 in (250 mm)	0.06 in (1.40 mm)	19 TPI	0.02 in. (0.6 mm)		★	★★	★		
					0.04 in. (0.9 mm)		★★	★★			
⑥ GNB-230 JAPANESE-CUTTING TEMPERING DISCO DRIVE IMPULSED BLADE COAT (PULBLC)	MICRO FINE CUT	9.1 in (230 mm)	0.05 in (1.20 mm)	21 TPI	0.02 in. (0.5 mm)		★	★★	★		
					0.03 in. (0.7 mm)		★★	★★			

★★★ Best ★★ Better ★ Good

PULL-STROKE SAWS

JAPAN PULL™ G-SAW

All handles are interchangeable with all blades.



BLADE						MATERIAL SUITABILITY INDEX					
	CUT	BLADE LENGTH	TOOTH PITCH	TPI	BLADE THICKNESS KERF WIDTH						
① ALB-A240	AGGRESSIVE CUT	9.4 in (240 mm)	0.1 in (3.0 mm)	9 TPI	0.04 in. (0.9 mm)	★★		★★	★	★★	
② ALB-A270		10.6 in (270 mm)			0.05 in. (1.2 mm)	★★		★★	★	★★	
③ GKB-G210		8.3 in (210 mm)			0.03 in. (0.7 mm)	★★		★★	★	★★	
④ GKB-G240		9.4 in (240 mm)			0.04 in. (1.0 mm)	★★		★★	★	★★	

★★★ Best ★★ Better ★ Good